

KOWOBRITE X

Darkroom Safe Light
KOWOBRITE X



Magnificent Illumination
of Darkrooms

KOWOBRITE X – very bright dark room safe light

Long adaption times of the eyes up to five minutes are history with the new KOWOBRITE X. Although the safe light is very bright there is no exposure of X-Ray films (streaks). The „red light“ from KOWOBRITE X has only a wave length not effecting X-ray films. With built-in dimmer, brightness can be controlled to the desired level. The strong mounting support allows wall or ceiling installation for direct or indirect lighting.

Specification:

KOWOBRITE X

Power: 5 W
Control: 0 ... 100 %
Housing: plastics - IP 66 according to EN 60529
Mounting: wall / ceiling, tilt
Viewing screen: 135 x 80 mm
Dimensions: 200 x 110 x 60 / 105 mm
(WxHxD – without / with mounting support)

KOWOBRITE X 230

Voltage: 95 ... 240 V AC / 50 ... 60 Hz
Power cord: 1.5 m, EU type plug
Switch: On / Off in power cord

Article no. 12 30250

KOWOBRITE X 12

Voltage: 9 ... 34 V DC
Power cord: 1.8 m, with free ends (+ / -)
for mobile darkroom labs – vehicle type
Switch: no

Article no. 12 30260



KOWOWET X – waterproof wet film viewer

The KOWOWET X is used for initial check of just developed films directly mounted at the processing unit. The non-corrosive and waterproof plastic housing and the LEDs promise a very long and trouble free operation.

Specification:

KOWOWET X

Viewing area: 135 x 80 mm
Viewing screen: 155 x 100 mm - tempered glass
Luminance: 6,800 Cd/m²
Power: 8 W
Switch: push- or on/off
Housing: plastics - IP 66 according to EN 60529
Dimensions: 200 x 110 x 60 mm (WxHxD)

KOWOWET X 230

Voltage: 95 ... 240 V AC / 50 ... 60 Hz
Power supply: external with power cord

Article no. 12 30101

KOWOWET X 12

Voltage: 9 ... 34 V DC
Power cord: 1.8 m, with free ends (+ / -)
for mobile darkroom labs – vehicle type

Article no. 12 30100




Made in
Germany